

Rollomat

Escalator and moving pavement cleaner

- ▲ Special cleaner for mechanical cleaning of escalators and moving pavements
- ▲ Removes general, oily and greasy dirt
- ▲ Very low foaming, thus minimal foam even when used in high concentrations
- ▲ No dripping of the cleaning solution into the escalator shaft
- ▲ Very good wetting properties



Area of application

For mechanical cleaning of escalators and moving pavements made of lightweight metal using the brushing-vacuuming method.

Application

Please test on a small inconspicuous spot before first application. First brush off dry, thick dirt encrustations in the profile of the step/moving pavement elements. Dissolve residual soiling by pre-spraying using a pressure sprayer.

Brushing-vacuuming method:

1 L to 10 L of cold water.

Pour cleaning solution into the freshwater tank of the machine and use brushing-vacuuming method to clean the escalator or moving pavement. Prior to spraying, dilute the product 1:1 to 1:5 for heavy soiling.

Consumption depends on the floor cleaning machine used and the selected water flow rate.

Note

Kiehl accepts no liability or responsibility for damage caused as a result of incorrect use or application of the product. Not a consumer product according to 1999/44/EC Art. 1! For professional use only!

Ingredients (according to 648/2004/EC)

Nonionic surfactants < 5%, phosphates 5–15%, water-soluble solvents, additives, fragrances.

pH value (concentrate): approx. 10

pH value (ready-to-use solution): approx. 9.5

Art. No.	Packaging unit (PU)	Numbers of PU per pallet
j100510	10 L canister	60